

# Rittal – The System.

Faster – better – everywhere.

## **Wall-mounted cooling unit Blue e+ Total cooling output 2.00 – 6.00 kW – SK 3186.930**

Date : Jan 21, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wall-mounted cooling unit Blue e+ Total cooling output 2.00 – 6.00 kW – SK 3186.930

created: 21.01.2020 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Benefits:</b>	Average 75% energy savings thanks to speed-regulated components and heat pipe technology Suitable for international use due to a unique multi-voltage capability Longer service life of the components inside the enclosure and the cooling unit due to component-friendly cooling Intuitive operation due to touch display and intelligent interfaces
<b>Material:</b>	Sheet steel
<b>Colour:</b>	RAL 7035
<b>Protection category IP to IEC 60 529:</b>	Internal circuit IP 55
<b>Supply includes:</b>	Nano-coated condenser Integral electric condensate evaporation Assembly parts Fully wired ready for connection (plug-in terminal strip)
<b>Note:</b>	Please observe the mounting instructions. Firmware can be updated using the RiDiag III software (3159.300)
<b>Options:</b>	For remote monitoring and networking of cooling units and chillers in the Blue e+ generation, please use the IoT interface (Model No. 3124.300). Increase machine availability and process reliability with remote monitoring of device data, statuses and system messages.

## Product features

<b>Variant:</b>	wall-mounted
-----------------	--------------

<b>Total cooling output to DIN EN 14511:</b>	L 35 L 35 at 50 Hz: 2 kW L 35 L 35 at 60 Hz: 2 kW L 35 L 50 at 50 Hz: 1.29 kW L 35 L 50 at 60 Hz: 1.29 kW
<b>Rated power input:</b>	0.73 kW
<b>Air throughput (unimpeded air flow):</b>	External circuit: 1250 m³/h Internal circuit: 1250 m³/h
<b>Rated operating voltage:</b>	110 V - 240 V, 1~, 50 Hz/60 Hz 380 V - 480 V, 3~, 50 Hz/60 Hz
<b>Dimensions:</b>	Width: 450 mm Height: 1600 mm Depth: 294 mm
<b>Temperature control:</b>	e+ controller (factory setting +35 °C)
<b>Temperature range:</b>	Bearing: -40 °C...+70 °C Operation (environment): -20 °C...+60 °C Setting range: +20 °C...+50 °C
<b>Refrigerant/cooling medium:</b>	Refrigerant: R134a Quantity: 1150 g CO <sub>2</sub> equivalent (CO <sub>2</sub> e): 1.64 t
<b>Power consumption P<sub>el</sub>:</b>	L 35 L 35 at 50 Hz: 0.57 kW L 35 L 35 at 60 Hz: 0.57 kW L 35 L 50 at 50 Hz: 0.6 kW L 35 L 50 at 60 Hz: 0.6 kW
<b>Seasonal energy efficiency ratio (SEER) 50/60 Hz:</b>	8.1
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	55.2 kg
<b>EAN:</b>	4028177709584
<b>Customs tariff number:</b>	84158200
<b>ETIM 7.0:</b>	EC000855
<b>ETIM 6.0:</b>	EC000855
<b>eCl@ss 8.0/8.1:</b>	27180704
<b>eCl@ss 6.0/6.1:</b>	27180704

**Product description:** SK cooling unit Blue e+, wall-mounted, 2 kW, 110-240 V, 1~, 380-480 V, 3~, 50-60 Hz, Sheet steel, WHD: 450 x 1600 x 294 mm

## Approvals

<b>Approvals:</b>	Approval overview UL + C-UL - FTTA	TÜV-tested safety UL + C-UL
-------------------	---------------------------------------	--------------------------------

<b>Certificates:</b>	EAC
----------------------	-----

<b>Declarations:</b>	Declaration of conformity Declaration of conformity - F-gas regulation
----------------------	---